

ECHNICAL TOOL



NATURE SERIES

NATURE-XXX



Information:

- 1. TECHNICAL INFORMATION
- 2. PRODUCTS AVAILABLE FROM STOCK
 - 3. MARKETING MATERIAL

MRK-012-0043

1. TECHNICAL INFORMATION

• TECHNICAL DATA

Chemical nature	Polyester	
Finish	Smooth matt	
UV resistance	Suitable for outdoor use	
Covered area per unit weight	13,1 m ² /Kg	
Specific weight	1,27 ± 0,03 g/cm ³	

• APPLICATION AND CURING CYCLE

Available for corona charging.

Curing time and temperature:

- 20 minutes at 180°C – 356°F (metal temperature).

Recommended thickness: 60-80 micron.

The special formulation of this product gives a finish always different and uneven, with a look 'nature'.

• MECHANICAL PROPERTIES

Test	Standard Reference	Result
Buchholz	ISO 2815	ok
Cross-cut	ISO 2409	no loss of adhesion: ok
Impact 2,5 N*m	ISO 6272	ok
Bending	ISO 1519	no loss of adhesion: ok
Salt spray	ISO 9227	corrosion <4 mm: ok

PACKAGING







Cardboard packaging; standard box 25 kg net weight; minibox for smaller quantity also available.


2. PRODUCTS AVAILABLE FROM STOCK

NATURE-001	NATURE-002	NATURE-003
NATURE-004	NATURE-005	NATURE-006

NATURE-007 NATURE-008

3. MARKETING MATERIAL







set of 8 aluminium coated panels

A FREE catalogue size A4 with aluminium decorated samples, or a set of 8 aluminium coated panels, will be delivered with every purchase order for 25 kg of product.

The marketing material can be customized, on demand.