



METALOOK SERIES

Bonded powder coatings with metal effects



Information:

- 1. TECHNICAL INFORMATION
- 2. PRODUCTS AVAILABLE IN STOCK
 - 3. MARKETING MATERIAL

MRK-012-0108rev01

Bonded powder coatings with metal effects

1. TECHNICAL INFORMATION

• PRODUCT FEATURE

The powders of the *Metalook* series are characterized by extraordinary metal effects with special tonalities and shades; these very particular results are obtained with the bonding technology.

• TECHNICAL DATA

Chemical nature	Bonded Polyester			
Finish	Smooth glossy			
Product	Steelook-001	Titanlook-001	Goldlook-001	Silverlook-001
Class of resistance	Not for outdoor	Not for outdoor	Not for outdoor	For outdoor use
Yield in surface/mass	7,9 m ² /Kg	•		
Specific weight	$1,27 \pm 0,03 \text{ g/cm}^3$			

• APPLICATION AND CURING CYCLE

Available for corona charging.

Curing time and temperature:

- 20 minutes at 180°C 356 F (metal temperature).
- 16 minutes at 190°C 374 F (metal temperature).
- 12 minutes at 200°C 392 F (metal temperature).

Recommended thickness: 80-90 micron.

• MECHANICAL PROPERTIES

Test	Standard Reference	Result
Buchholz	ISO 2815	ok
Cross-cut	ISO 2409	no loss of adhesion; ok
Impact 2,5 N*m	ISO 6272	ok
Bending	ISO 1519	no loss of adhesion; ok
Reverse impact test	ASTM D2794	ok

Bonded powder coatings with metal effects

2. PRODUCTS AVAILABLE IN STOCK

• PRODUCT CODE

STEELOOK-001 GOLDLOOK-001

TITANLOOK-001 SILVERLOOK-001

• PACKAGING



Cardboard packaging; net weight 20 Kg – Lower weight miniboxes are available

3. MARKETING MATERIAL



A3 catalogue with aluminum samples

With each 20 kg product order will be delivered a copy FOR FREE of the A3 catalogue with aluminum samples.

On demand, it is possible to customize the marketing material.

